



## Key Features:

- ◆ Receive push notifications and video clips (customizable length) on the app when the camera is triggered
  - ◆ Remote live streaming through the app to view real-time camera footage
  - ◆ Supports cloud storage (free 3-day loop) and Micro SD card (up to 128 GB) for video storage, Ability to save videos directly to your smartphone
  - ◆ Equipped with a solar panel for continuous power supply using sunlight, ensuring long-lasting performance without the need for camera removal or recharging
  - ◆ Built-in spotlight for color night vision in dark environments (triggered or manually activated), otherwise provides infrared black and white night vision
  - ◆ Built-in speaker for playing alarm sounds to deter intruders (triggered or manually activated)
  - ◆ Built-in stereo microphone for two-way audio communication (manually activated during live streaming)
- ◆ Strong WiFi signal with a range of up to 200 meters in open environments, ensuring stable connection
  - ◆ IP65 waterproof rating for excellent weather resistance
  - ◆ Supports multiple user sharing
  - ◆ Manual and scheduled automatic sleep modes for power-saving
  - ◆ Flexible installation options: wall-mounted or tabletop, with easy setup methods

## Smart Security Camera

SSC0A



## Technical Specifications of Camera

|                          |   |
|--------------------------|---|
| <b>Power Supply</b>      | Built-in rechargeable lithium battery + solar panel |
| <b>Solar Panel Power</b> | 3 W   |
| <b>Battery Type</b>      | Rechargeable lithium battery × 1 (non-replaceable)  |
| <b>Charging Voltage</b>  | 5 V DC  |
| <b>Charging Current</b>  | 1.5 A   |
| <b>Battery Capacity</b>  | 5,000 mAh   |

|  |   |
|--|---|
| <b>Product Life</b>                        | Depends on the number of battery cycles it goes through   |
| <b>Battery Life</b>                        | About 6 months (20 daily videos, each lasting 10 seconds)   |
| <b>Mounting Methods</b>                    | Screws  |
| <b>Installation Locations</b>              | Indoors/Outdoors  |
| <b>Indicator Light</b>                     | Blue, yellow, green, red  |
| <b>Number of Devices That Can Be Added</b> | 24 cameras of a single model under a house can be added at most   |
| <b>Wi-Fi Frequency</b>                     | 2.4 GHz (incompatible with 5 GHz Wi-Fi network)   |
| <b>Wi-Fi Transmission Range</b>            | 656 ft (200 m) in open air  |
| <b>Operating Temperature</b>               | Charging temperature: 32–113 ° F (0–45°C)   |
|  | Working temperature: 14–113 ° F (-10–45°C)  |
|  | Storage temperature: -4–140 ° F (-20–60°C)  |
| <b>Resolution</b>                          | 1080p (1920 × 1080)   |
| <b>Field of View</b>                       | Diagonal: 130 °   |
| <b>Night Visibility</b>                    | The color night vision can cover up to 23 ft (7 m) when the spotlight is turned on to illuminate.   |
| <b>PIR Detection</b>                       | Built-in PIR sensor with a detection angle of up to 90 °  |
| <b>PIR Distance</b>                        | Sensitivity setting: high: 23–26 ft (7–8 m), medium: 16–20 ft (5–6 m), low: 10–13 ft (3–4 m) (for standard installation). Please note that the PIR distance may be reduced by 3.3–6.6 ft (1–2 m) due to temperature factors.  |
| <b>Lighting</b>                            | Spotlight (color night vision)  |
|  | Infrared LEDs (black and white night vision)  |
| <b>Voice</b>                               | HD noise-canceling microphone and two-way intercom  |
| <b>Product Weight</b>                      | 232g  |
| <b>Product Dimensions</b>                  | 67 x 58 x 89mm  |
| <b>Package Contents</b>                    | 1 × Security Camera + 1 × USB Charging Cable + 1 × Camera Mounting Bracket + 1 × Camera Screw Kit + 1 × Solar Panel + 1 × Solar Panel Universal Joint + 1 × Solar Panel Socket Nut + 1 × Solar Panel Base + 1 × Solar Panel Locking Screw Cap + 1 × Solar Panel Screw Kit + 1 × User Manual |

# Technical Specifications of Solar Panel

|                              |                     |
|------------------------------|---------------------|
| <b>Cable Length</b>          | 9.2 ft (2.8 m)      |
| <b>Operating Voltage</b>     | 5 V DC              |
| <b>Operating Temperature</b> | -5–120°F (-20–49°C) |

## Working Modes

|                               |                            |
|-------------------------------|----------------------------|
| <b>Working Mode</b>           | Blue light is always on.   |
| <b>Sleep Mode</b>             | Light off.                 |
| <b>Charging Mode</b>          | Yellow light is always on. |
| <b>Charging Complete Mode</b> | Green light is always on.  |

## Ordering Information

| Part Number | Pack Quantity | Dimension         | Weight | Units/Carton |
|-------------|---------------|-------------------|--------|--------------|
| SSC0A       | 1 pack        | 245 x 140 x 128mm | 920g   | 18 units     |

# Deltronic



Deltronic Security AB  
EA Rosengrängsgata 4  
421 31 Västra Frölunda  
Sverige  
+46-31-140800  
[www.deltronic.se](http://www.deltronic.se)  
[info@deltronic.se](mailto:info@deltronic.se)